

Refine Search

Search Results -

Terms	Documents
L17 and L8	1

Database:

US Pre-Grant Publication Full-Text Database
 US Patents Full-Text Database
 US OCR Full-Text Database
 EPO Abstracts Database
 JPO Abstracts Database
 Derwent World Patents Index
 IBM Technical Disclosure Bulletins

Search:

L18

Refine Search

Recall Text

Clear

Interrupt

Search History

DATE: Friday, October 01, 2004 [Printable Copy](#) [Create Case](#)

Set Name Query
 side by side

Hit Count Set Name
 result set

DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI; PLUR=YES; OP=OR

<u>L18</u>	L17 and l8	1	<u>L18</u>
<u>L17</u>	foil near packet	604	<u>L17</u>
<u>L16</u>	contraceptives near packag\$	50	<u>L16</u>
<u>L15</u>	((intravaginal or vaginal) adj ring) near packag\$	1	<u>L15</u>
<u>L14</u>	L13	46	<u>L14</u>
<u>L13</u>	L12 and l8	46	<u>L13</u>
<u>L12</u>	packages and contraceptives	1351	<u>L12</u>
<u>L11</u>	contraceptive near packages	28	<u>L11</u>
<u>L10</u>	L9 and (hermetically)	3	<u>L10</u>
<u>L9</u>	L8 and (pack\$ or bag)	96	<u>L9</u>
<u>L8</u>	(intravaginal or vaginal) adj ring	361	<u>L8</u>
<u>L7</u>	L6 and package	55	<u>L7</u>
<u>L6</u>	vaginal adj ring	327	<u>L6</u>
<u>L5</u>	vagnal adj ring	0	<u>L5</u>

[First Hit](#) [Previous Doc](#) [Next Doc](#) [Go to Doc#](#)

Generate Collection

Print

L4: Entry 29 of 32

File: JPAB

Aug 22, 1995

PUB-NO: JP407223653A

DOCUMENT-IDENTIFIER: JP 07223653 A

TITLE: BAG FOR PACKING

PUBN-DATE: August 22, 1995

INVENTOR-INFORMATION:

NAME

COUNTRY

MATSUO, TOSHIO

NAKAJIMA, YOICHI

IWAHASHI, HIDEAKI

HARA, KAZUYA

ASSIGNEE-INFORMATION:

NAME

COUNTRY

HISAMITSU PHARMACEUT CO INC

APPL-NO: JP06037648

APPL-DATE: February 10, 1994

INT-CL (IPC): B65 D 33/00; B65 D 33/25

ABSTRACT:

PURPOSE: To make unsealing easy while improving tightness in sealing for a bag made of a laminated body by a method wherein a dashed line for tearing-up provided to a position above a zipper is made in a specified structure.

CONSTITUTION: In a packaging body 1, seals 2 are provided to its periphery, a zipper 3 is provided transversely on the upper part of the bag and a dashed line 4 for tearing-up is provided to a position above the zipper 3. The bag 1 is constructed of a laminated body, a compound aluminum made at least of two layers, and the aluminum is desirable to be included in the inside layer in order to provide excellent airtightness to the bag 1. The dashed line 4 for tearing-up is formed at least to one layer on the outside of the layer constituting the laminated body, and is not formed to the inside layer formed at least of one layer. Thereby, a part above the zipper 3 can be cut easily while keeping airtightness for the bag, and contents in the package can be preserved stably.

COPYRIGHT: (C)1995,JPO

[Previous Doc](#) [Next Doc](#) [Go to Doc#](#)